



## **BIG SOUND IN A SMALL PACKAGE**

### FULL RANGE, ALL-ENVIRONMENT OUTDOOR SPEAKER

The **NEAR**<sup>®</sup> LB4TM loudspeaker is elegantly designed, rugged to the extreme, and a snap to install. In fact, it offers two mounting methods: our Signature (Ball & Socket) wall-mount bracket, and the very handy stake-mounting accessory for installation in gardens and around other outdoor entertainment areas. The LB4TM shares the same advanced technologies as the other NEAR LB Series models, including metal-alloy speaker cones and dense-packed mica-filled polypropylene enclosures.

This **NEAR** outdoor speaker system is extremely versatile and allows for imultiple configurations. You can give any client the ultimate in sound for outdoor entertaining, whether a palatial estate or a modest backyard.

For more information, call your **NEAR** sales representative today at (855) 350-6327 or please visit our website at **www.nearspeakers.com.** 



NEAR is a Division of Bogen Communications, Inc.

# **LB4TM** ALL-ENVIRONMENT, HIGH PERFORMANCE OUTDOOR SPEAKER

#### FEATURES

- Purpose-built to be extremely durable in all weather conditions
- Anodized metal-alloy speaker cones (MDT) are extremely stable
- Waterproof (IP68) input connector (included) eliminates long-term connection problems
- · MLS Ferrofluid voice coil centering system
- · Fluid-sealed gap eliminates corrosion in magnet
- Dual-layer voice coil with inside and outside windings for ultra-low distortion
- Mineral-filled polypropylene cabinet for durability and rigidity
- Advanced polymer cone surrounds resist UV rays, chlorine, fertilizer and salt spray
- Powder-coated bracket features a ball-and-socket easy-mount design
- Specially developed hydrophobic fabric port covers prevent entry of water, debris and small creatures
- Color: Mulch Brown



#### SPECIFICATIONS

| Frequency Response  |
|---|
| Sensitivity (1W/1m)   |
| Dispersion Minimum 120 Degrees, Horizontal & Vertical   |
| Power Requirements (LB4TM @16 ohms) Up to 75 Watts (Ave); 300W Peak   |
| Power Requirements (LB4TM @70V) 32W, 16W, 8W, 4W, 2W, 16 ohms   |
| Dimensions 5.51"W x 10.25"H x 6.3"D;<br>14cm W x 26cm H x 16cm D  |
| Product Weight (w/ mounting yoke & clamp)LB4T: 4.5lbs/2.04kgs   |
| Maximum SPL @1m (1/2 space) 105dB   |
| Input Terminations Waterproof Plug-In Connector (IP68 Rating)   |
| EnvironmentalEngineered to Meet or Exceed Mil-Std-810<br>(Humidity, Salt Air, Heat, Cold, Immersion); IEC IP 56 |

#### SPEAKER COMPLEMENT:

- (1) 4.5" Metal-Alloy Diaphragm Woofer, MLS Voice Coil Guidance, UV and Chemical-Resistant Rubber Surround
- (1) 1.1" Metal-Alloy Diaphragm Tweeter, Ferrofluid Damping, UV and Chemical-Resistant Rubber Surround, Corrosion-Resistant Magnet Assembly



8 ABJ Drive • Gardiner, ME 04345 • USA • Tel: (855) 350-6327 • www.nearspeakers.com NEAR is a Division of Bogen Communications, Inc.

© 2013-2016, Specifications are subject to change.