

Studio sound comes home

Featuring a Carbon Dome™ tweeter in a solid-body housing and a decoupled Continuum™ midrange, the 700 Series' flagship floorstander brings studio-quality sound to your home audio set up. The speaker relays textural details with goosebump-inducing accuracy, making even largescale recordings sound stunningly lifelike.

Technical Specifications

Description 3-way vented-box system

Technical features Decoupled Carbon Dome™ tweeter

Solid Body Tweeter on top

Continuum™ cone FST™ midrange

Decoupled midrange Aerofoil™ Profile bass cones

Flowport™

Drive units 1x ø25mm (1 in) Decoupled Carbon

Dome high-frequency

1x ø150mm (6 in) Continuum cone

FST midrange

3x ø165mm (6.5 in) Aerofoil Profile bass

Frequency range (-6dB) -6dB at 28Hz and 33kHz

Frequency Response -3dB 45Hz - 28kHz ±3dB

Sensitivity 90dB spl (2.83V_{RMS}, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 86Hz - 28kHz <0.5% 110Hz - 20kHz

Nominal impedance 8Ω (minimum 3.1Ω)

Recommended amplifier

power

30W - 300W into 8Ω on unclipped

programme

Dimensions Height: 994mm (39 in) cabinet only

1087mm (42.8 in) including

tweeter and plinth

Width: 200mm (7.9 in) cabinet only

366mm (14.4 in) including plinth

Depth: 337mm (13.3 in) cabinet only

364mm (14.3 in) including grille

and terminals

452mm (17.8 in) including plinth

Net weight 29.5kg (65 lb)

Finishes Cabinet: Rosenut

Gloss Black Satin White

Grille: Black

Grey (Satin White only)

Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST, Aerofoil and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE

This information is intended as a guide only and reflects the current specification at the time of print. We reserve the right to make changes to the specifications



