

Studio sound comes home

With state of the art features such as the tweeter-ontop design borrowed from the 800 Series Diamond, this uncompromising high performance two-way speaker reveals subtle nuances in music others miss. Even challenging instruments such as the piano are conveyed with uncanny realism, presence and transparency.

Technical Specifications

Description 2-way vented-box system

Technical features Decoupled Carbon Dome™ tweeter

Solid Body Tweeter on top

Continuum™ cone bass/midrange

Flowport™

Drive units 1x ø25mm (1 in) Decoupled Carbon

Dome high-frequency

1x ø165mm (6.5 in) Continuum cone

bass/midrange

Frequency range (-6dB) -6dB at 45Hz and 33kHz

Frequency Response -3dB 50Hz - 28kHz ±3dB

Sensitivity 88dB spl (2.83V_{RMS}, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 100Hz - 22kHz <0.5% 150Hz - 20kHz

Nominal impedance 8Ω (minimum 3.7Ω)

Recommended amplifier

power

30W - 120W into 8Ω on unclipped

programme

Dimensions Height: 340mm (13.4 in) cabinet only

407mm (16 in) including tweeter

Width: 200mm (7.8 in)

Depth: 285mm (11.2 in) cabinet only

310mm (12.2 in) including grille

and terminals

Net weight 9.3kg (20.5 lb)

Finishes Cabinet: Rosenut

Gloss Black Satin White

Grille: Black

Grey (Satin White only)

Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST and Flowport are trademarks of B&W Group Ltd.





