

Studio sound comes home

Small speaker, big sound. Ideal for smaller rooms, and designed for use on bookshelf or stand, the 707 produces tremendous highs and depths for a compact unit. Its two-way design and advanced drive units make for a sound that's clear, powerful and remarkably cohesive.

Technical Specifications

Description 2-way vented-box system

Technical features Decoupled Carbon Dome™ tweeter

Continuum[™] cone bass/midrange

Flowport™

Drive units 1x ø25mm (1 in) Decoupled Carbon

Dome high-frequency

1x ø130mm (5 in) Continuum cone

bass/midrange

Frequency range (-6dB) -6dB at 45Hz and 33kHz

Frequency Response -3dB 50Hz - 28kHz ±3dB

Sensitivity 84dB spl (2.83V_{RMS}, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 110Hz - 22kHz

Nominal impedance 8Ω (minimum 4.0Ω)

Recommended amplifier

power

30W - 100W into 8Ω on unclipped

programme

Dimensions Height: 280mm (11 in)

Width: 165mm (6.5 in)

Depth: 260mm (10.2 in) cabinet only

276mm (10.9 in) including grille

and terminals

Net weight 6.0kg (13.2 lb)

Finishes Cabinet: Rosenut

Gloss Black Satin White

Grille: Black

Grey (Satin White only)

Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST and Flowport are trademarks of B&W Group Ltd.





