# MHUB PRO (4x4) 40

**Product code: MHUBPRO4440 HDMI / HDBaseT Matrix System** 



















Connectivity-rich professional series 4x4 HDMI/HDBT+mirror matrix system with long-range video (4K 40m/1080p 70m) and powerful control options. A 'one-wire' UHD/4K-capable whole-home AV hub, that hides home entertainment devices centrally and makes them universally available on every display.

All easily-controlled via the free uControl app or with the hands-free convenience of Alexa voice control - also features remote monitoring and management via HDA Cloud, designed to reduce the necessity for callouts and site visits. Capable of carrying Ultra HD 4K + support for HDR and Dolby Vision®. Integration needs are well catered for, with each of the four display outputs featuring both multichannel digital audio extraction and stereo downmixing, making for easy integration with multizone amplifiers or audio matrices.

#### **FEATURES**

HDMI® 2.0 features supported up to 10.2Gbps		
Backlit fade in/out touch panel controls		
All display receivers powered via PoH		
Web GUI for easy config and setup (MHUB-OS)		
Remote system monitoring and management (HDA Cloud)		
Advanced EDID management		
Supports HDCP 2.2 Ultra HD 4K 24/30Hz 4:2:2 (HDR10) or 60Hz 4:2:0 (HDR 8bit) + support for Dolby Vision and HLG.		
Supports all current audio formats up to and including Dolby Atmos® and DTS:X®		
Multichannel audio extraction via digi-coax, or audio downmix via stereo jack		
Easy and instant integration with MHUB AUDIO		
4K>1080 down/up-scaling receiver option available		

### **SPECIFICATIONS**

Form factor	19"/1U aluminum rack-mountable unit
Inputs x outputs	4 HDMI x 4 RJ45 HDBaseT + 4 mirrored HDMI
Transmission tech.	HDBaseT Class B and HDMI
Video bandwidth	340MHz clock / 10.2Gbps data
ESD protection	± 8kV (air-gap discharge) ± 4kV (contact discharge)
Hub control	Web GUI, IR, TCP/IP, RS232, App, Alexa
App control	Full control over sources, matrix hub & display functions.
Device weight	Hub 2400g RX 125g
Package weight	3500g
Dimensions (W/D/H)	Hub 440 / 284 / 45mm (without feet) RX 140 / 65 / 17mm
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	-4°F to 140°F (-20°C to 60°C)
Relative humidity	20~90 % RH (non-condensing)
Power consumption	30W (max) 0.5W (standby)
Guarantee	3/4-year guarantee (Cloud registration required)

### CONTROL









## MHUB PRO 40

**Product Code: MHUBPRO4440** 

### **LEGEND**















