

DETECTING FIRE RISKS IN THE FIRST PLACE

Performance Series Thermal Bi-spectrum Turret Camera


KEY FEATURES



Temperature exception alarm
with visualized smart warning



Vigilant smoking detection
helps to detect smoking
behaviors in the first place



Video Content Analytics
with deep learning
algorithms to reduce false
alarms



Picture-in-picture preview
saves efforts on switching
between optical and thermal
channels

APPLICATION SCENARIOS



Warehouses



Substations



Data Centers



Factories



Pump Rooms



Villas



Recycling Centers



Parking Lots

PARAMETERS

DS-2TD1217-2/V1

DS-2TD1217-3/V1

DS-2TD1217-6/V1

Performance Series Thermal Bi-spectrum Turret Camera



- Resolution:
 - Thermal: 160 x 120 @ 25 fps, 17 μ m (the resolution of the output image is 320 x 240)
 - Optical: 1920 x 1080
- Focal length:
 - Thermal: 2 mm / 3 mm / 6 mm
 - Optical: 2 mm / 4 mm / 6 mm
- Hikvision sensor, NETD < 40 mk
- Video content analytics: Line crossing / Intrusion detection / Region entrance / Region exiting
- Smoking detection
- Supports bi-spectrum image fusion, picture-in-picture preview
- Temperature exception alarm (temperature measuring range: -20° to 150° C, accuracy: \pm 8° C)
- Working temperature: -40° to 65° C (-40° to 149° F)
- IP67 ingress protection



Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

