

FULL RANGE, ALL-ENVIRONMENT BRACKET-MOUNT SPEAKER

The **NEAR**® LB5 speaker is elegantly designed, rugged to the extreme and a snap to install. The LB5 employs a **NEAR** exclusive "lever bracket" mount combined with a perfect-fit, totally waterproof input connector. This mounting system minimizes installation effort and reduces "ladder time" to improve installation safety. The LB5 utilizes MDT/MLS woofers with 1" titanium inverted dome tweeters for timbre consistency across the range to allow for complete system design flexibility. The LB5 enclosure is color-through, micaloaded polypropylene with color-matched aluminum grille. Water-shedding and dust-protecting hydrophobic fabric prevents ingress of fine debris.



The LB Series speakers quickly and easily slide into slots in the clamp module, with knobs and bracket preattached to the speaker. The knobs are also oversized for easier grip and better control during installation. The

speaker assembly comes with a pre-terminated waterproof plug-in connector that makes installation a breeze.

For more information, call your **NEAR** sales representative today at (855) 350-6327 or please visit our website at **www.nearspeakers.com**.





ALL-ENVIRONMENT OUTDOOR BRACKET-MOUNT SPEAKER

FEATURES

- Purpose-built to be extremely durable in all weather conditions
- Anodized metal-alloy speaker cones (MDT) are extremely stable
- Waterproof (IP68) input connector (included) eliminates long-term connection problems
- MLS Ferrofluid voice coil centering system
- Fluid-sealed gap eliminates corrosion in magnet
- Dual-layer voice coil with inside and outside windings for ultra-low distortion
- Mineral-filled polypropylene cabinet for durability and rigidity
- Advanced polymer cone surrounds resist UV rays, chlorine, fertilizer and salt spray
- Heavy-gauge, powder-coated aluminum mounting bracket with unique (patent-pending) cast aluminum lever-mount clamp
- 70V transformer version available (LB5T) for use with the NEAR 6XL power amplifier or equivalent
- Specially developed hydrophobic fabric port covers prevent entry of water, debris and small creatures
- · Colors: Available in black and white (both paintable)



SPECIFICATIONS

Frequency Response55Hz to 19kHz, +/-2.5dB
Sensitivity (1W/1m)
Dispersion Minimum 120 Degrees, Horizontal & Vertical
Power Requirements (LB5 @8 ohms)Up to 75 Watts (Ave); 300W Peak
Power Requirements (LB5T @70V)32W, 16W, 8W, 4W, 2W or 8 ohms
Dimensions
Product Weight (w/mounting yoke & clamp)LB5: 7lbs/3.18kgs; LB5T: 8lbs/3.63kgs
Maximum SPL @1m (1/2 space)106dB
Input Terminations Waterproof Plug-In Connector (IP68 Rating)
EnvironmentalEngineered to Meet or Exceed Mil-Std-810 (Humidity, Salt Air, Heat, Cold, Immersion); IEC IP 66

SPEAKER COMPLEMENT:

- (1) 5.25" Metal-Alloy Diaphragm Woofer, MLS Voice Coil Guidance, UV and Chemical-Resistant Rubber Surround
- (1) 1.1" Metal-Alloy Diaphragm Tweeter, Ferrofluid Damping, UV and Chemical-Resistant Rubber Surround, Corrosion-Resistant Magnet Assembly

