



TRIBUTARIES®

Bringing it all together



T100 & T200

POWER
MANAGERS

T100 & T200

The Tributaries® T100 and T200 will provide clean, surge protected AC power to your valuable audio, video and home theater components. Features that are common to both units include:

- 1800 watt / 15A Rating
- Analog, Digital and High Current AC Outlets
- Front Panel Convenience AC Outlet
- Always-on, Switched and Delayed AC Outlets
- Remote Triggering
- USB Outlets, Front & Rear with USB Lamp
- Dimmable Front Panel LEDs
- Suitable for Rack Mounting
- AC Line Surge Protection
- Over Voltage and Under Voltage Protection
- Telecom Surge Protection
- Cable TV and Satellite TV Surge Protection
- Front Panel Systems LEDs & Meters
- Multiple UL® Listings
- \$25,000 Connected Equipment Warranty
- RoHS Compliant

T100 Features:

T100, the 9 AC Outlet Solution. Designed for audio/video & home theater systems which require a full solution surge suppressor as well as an effective line filtering device, the Tributaries T100 is the answer.



Front Panel



Back Panel

- 1U rack mountable Power Manger
- 4320 Joule Rating
- 9 Outlets:
 - 2 isolated Always-on Digital banks
 - 1 isolated Switched-on Analog bank
 - 1 isolated Delayed-on High Current bank
 - 1 Always-on Convenience outlet (front)
- 2 DSS/CATV protected lines
- 2 second delay power switch for control turn-on
- 12 volt DC trigger in and out
- Dimmable front panel

2 USB charging outlets with a complimentary USB goosneck light with magnet to store when not in use to illuminate dark racks.

T200 Features:

T200, the 13 AC Outlet Upgrade Solution. For the system that requires a higher level of filtering, surge suppression and number of outlets, the Tributaries T200 will fill those needs.



Front Panel



Back Panel

- 2U rack mountable Power Manager
- 5400 Joule Rating
- 13 Outlets:
 - 2 isolated Always-on Digital banks
 - 1 isolated Switched or Always-on Digital bank
 - 2 isolated Switched-on Analog banks
 - 1 Delayed-on High Current bank
 - 1 Always-on Convenience outlet (front)
- 3 DSS/CATV protected lines
- 2 second delay power switch for control turn-on
- 12 volt DC trigger in and out
- Dimmable front panel

2 USB charging outlets with a complimentary USB goosneck light with magnet to store when not in use to illuminate dark racks.